

Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Ricoh	Logo
Company name *	Ricoh Company Ltd.	
Contact information * e-mail address	Ricoh Europe Plc, 20 Triton Street, London NW1 3BF	
Internet site *	www.ricoh.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.						
Type of product *	Colour Printer					
Commercial name *	P C600					
Model number *	P C600					
Issue date *	8th th May 2019					
Intended market *	🗌 Global 🔀 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

Model nu	Model number * P C600		Logo			
Issue dat	ue date * 8th th May 2019					
Product	Require		met			
Item				Yes	No	n.a.
P1		bus substances and preparations				
P1.1*		s do comply with the current European RoHS Directive. (See legal reference and N	OTE B1)		<u> </u>	
P1.2*		s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.		\boxtimes		
P1.3*		the Legan reference has no maximum concentration value.		\square		
1 1.0		profluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrach	nloride, 1,1,1-			
		ethane, methyl bromide (see legal reference). Comment: Legal reference has no n				
	concenti	ration values.				
P1.4*		s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych	nlorinated	\boxtimes		
P1.5*		I (PCT) in preparations (see legal reference). 6 do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 car	hon atoms in the	\square		
11.5		ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).				
P1.6*	Parts wit	th direct and prolonged skin contact do not release nickel in concentrations above (0,5 µg/cm ² /week	\square		
		al reference).		_	_	
		nt: Max limit in legal reference when tested according to EN1811:2011-5.				
P1.7*		Article 33 information about substances in articles is available at (add URL or mail	contact):	\bowtie		
		icoh-europe.com				
P2	Batterie		a 1 1			
P2.1*		oduct contains a battery or an accumulator, the battery/accumulator is labeled with Information on proper disposal is provided in user manual. (See legal reference)	the disposal	\bowtie		
P2.2*		s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadn	nium (See legal	\square		
	referenc					
P2.3*	Batteries	and accumulators are readily removable. (See legal reference)		\boxtimes		
P3	Conform	nity verification & Eco design (ErP)				
P3.1*		duct is CE-marked to show conformance with applicable legal requirements (see leg		\square		
D2 0*		laration of Conformity can be requested at (add link or e-mail address): emo@rico	h-europe.com			
P3.2*		duct complies with the Eco design requirements for energy-related products, al reference).			\bowtie	
		d information is; given in item P15 or added to this document,				
	. to quiret	available at (add URL):				
P4	Consum	nable materials				
P4.1*	If a phot	o conductor (drum, belt etc.) is used in the product, it does not contain cadmium ma	ax 0,01% (see	\square		
	legal refe	erence and NOTE B1).				
P4.2*	If ink/ton	er is used in the product, it does not contain cadmium max 0,1% by weight (see leg	gal reference).	\boxtimes		
P4.3*		/toner formulation/preparation is classified as hazardous or contains a substance for		\square		
		munity workplace exposure limits, the product/packaging is adequately labeled acc		_	_	
		le regulations and a Safety Data Sheet (SDS) in accordance with these requirement	nts is available			
P5		al reference). : packaging				
P5.1*		ng and packaging components do not contain more than 0,01% lead, mercur	v cadmium and			
	hexavale	ent chromium by weight of these together.				
P5.2*		kaging materials are marked with abbreviations and numbers indicating the nature be legal reference).	of the material(s)	\square		
P5.3*		duct packaging material is free from ozone depleting substances as specified	in the Montrea			
. 0.0		(see legal reference).				
		ht: Legal reference has no maximum concentration values.				
P6	Treatme	nt information				
P6.1*	Informati	on for recyclers/treatment facilities is available (see legal reference).		\boxtimes		

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model n	umber *	P C600	Logo				
Issue date *		8th May 2019					
	Environn	mental attributes - Market requirements (See General NOTE GN below) nental conscious design		Require	ement	met	
Item		tory to fill in. Additional information regarding each item may be found under P14.		Yes	No	n.a.	
P7	Design	nbly roovaling					
P7.1*		nbly, recycling t have to be treated separately are easily separable					
P7.2*		aterials in covers/housing have no surface coating.			╞	<u> </u>	
P7.3*		arts > 100 g consist of one material or of easily separable materials.			⊢⊢		
P7.4*		arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.			⊢⊢	- H-	
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly ava	ailable tool		⊢⊢	-	
P7.6*		e easily separable. (This requirement does not apply to safety/regulatory labels).		<u>. </u>	╞	- #-	
17.0	Product						
P7.7*		g can be done e.g. with processor, memory, cards or drives					
P7.8*		g can be done using commonly available tools			H	- 2	
P7.9.		rts are available after end of production for: 7 years				<u> </u>	
P7.10		s available after end of production for: 7 years				-	
11.10		and substance requirements					
P7.11*	Product of	over/housing material type (e.g. plastics, metal, aluminum):					
P7.12	Material type: PC Material type: AS Material type: Insulation materials of external electrical cables are PVC free. Image: Comparison of the second sec						
P7.13		materials of internal electrical cables are PVC free.				- #-	
P7.14	External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts						
P7.15	Printed of	g more than 25% post-consumer recycled content. ircuit boards, PCBs (without components) are low halogen: all PCBs > 25 as defined in IEC 61249-2-21. (See NOTE B2)	g 🗌 are	low			
P7.16		tarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:					
P7.17	<u>Alt. 1: Ch</u> TBBPA (a <u>Alt. 2: C</u> h	emical specifications of flame retardants in printed circuit boards (without component	CAS #:				
P7.18	Alt. 1: Fla	g ISO 1043-4: ame retarded plastic parts > 25 g contain the following flame retardant substances/ ations above 0,1%:	preparatio	ns in			
	2. Chemi 3. Chemi	cal name: , CAS #: (See NOTE B4) cal name: , CAS #: " cal name: , CAS #: " nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-	4: FR ma	urk 🖂			
P7.19	In plastic	parts > 25 g, flame retardant substances/preparations above 0,1% are used which h the following Risk phrases; and Hazard statements:	ave been				
			OTE B5)			_	
P7.20*	lf YES; a a) Of to	umer recycled plastic material content is used in the product (See NOTE B6): t least one of the two alternatives below shall be answered; tal plastic parts' weight > 25 g, the postconsumer recycled plastic material content (entage of total plastic by weight) is 1.05% .	calculated	as a			
	or	weight of recycled material is g.					

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model nu	mber *	P C600				Logo				
Issue dat	le date * 8 th May 2019									
Product	environr	nental atti	ributes - Market re	quirements (cont	inued)		Re	auire	ement	met
Item				(Yes	No	n.a
	Material	and substa	ance requirements (c	ontinued)						
P7.21*	P7.21* Biobased plastic material content is used in the product (See NOTE B7):						\boxtimes			
	a) Of t tota	total plastic	of the two alternatives parts' weight > 25 g, weight) is <i>0</i> %.		vered; material content (calcul	ated as a perce	entage of			
	or b) The	e weiaht of t	he biobased plastic ma	aterial is g.						
P7.22*	Light sou	urces are fre	ee from mercury, i.e. le becify: Number of lam	ess than 0,1 mg/lamp	o. num mercury content pe	r lamp:	ng	\square		
P8	Batterie				nam mercury content pe	riamp.	iig			
P8.1*			mposition: Manganese	dioxide lithium batte	erv					
	Building C				.,					
P9		•	on (See NOTE B8)							
P9.1	For the p	product the	following power levels	or energy consumpt	ions are reported:					
Energy mo	ode *		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/St modes and te			energy	
Sleep moo STAR® O (OM) prod	perational		W	W	W					
Standby/o ENERGY	ff mode fo STAR Ope	erational	W	W	W					
Mode (OM) products TEC value for ENERGY STAR TEC products			kWh/week	kWh/week	0.55 kWh/week					
(TEC= Ty	pical Energ	ду								
Operating	g mode m	ono	W	W	628.2 W					
Operating	y mode co	olour	W	W	680.4 W	1				
Ready mo	ode		W	W	85.4 W					$\overline{\neg}$
Sleep mo	de		W	W	0.53 W					Ē
			W	W	W					⊢
			W	W	W					늼
Extornal	lower Sur		y Level (International							
		-			1010001) .					\square
Print/Scar	Speed *		40 images per minute							
Default tin	ne to enter	energy sav	e mode: 1 minutes							
P9.2*	Informat	ion about th	e energy save function	n is provided with the	e product.			\boxtimes		
P10	Emissio	ons								
	Noise e	mission – [Declared according to							
P10.1	Mode	M	ode description		tatistical upper limit A-w	eighted sound	power level	,		
	Idle	*	Stand-by	*	3.4					
	Operatio	n * (Operating mode mon							
	Other m	ode	Operating mode colo	ur	6.9					
Measured accordin				ECMA-74 (only if not covered b	by ECMA-74)					

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Model nu	mber *	P C600			Logo				
Issue dat	e *	8 th May 2019							
	environ	mental attributes	- Market requirements (cor	ntinued)				ment	
Item	Chamia		minting and ducto (Coo NOTE D	240)			res	No	n.a.
P10.2*			printing products (See NOTE E ECMA-328 Determination of Ch		a from Electronia				
	Equipm	ent (ISO/IEC 28360) , other specify: RAL-UZ 205	emical Emission Rates			\boxtimes		
P10.3	Typical	emission rate (opera	ation phase) is (mg/h):						
	Electrop	photographic device	s: Ozone 0.2 Dust 0.75	Styrene 0.78 Benze	ne <0.01 TVO	5.67			
	Ink devices: Dust Styrene Benzene TVOC								
	Note: co	ompliance with maxi	mum emission rates in eco labels	to be declared in P14	l.				
P11		mable materials for							
P11.1*		• • • •	is available for the ink/toner prep	•	• • •		\boxtimes		
P11.2*	EN 122	81.	sumer recycled fibers can be us		meets the require	ements of	\boxtimes		
P11.3*	2-sided	(duplex) printing/co	oying is an integrated product fun	ction.			\boxtimes		
P11.4*	The pro	duct is delivered to	end-user with default auto-duplex	enabled.			\boxtimes		
P13	Packag	ing and document	ation						
P13.1*	Product	packaging material packaging material packaging material	type(s): Corrugated Paper type(s): Cardboard & other pap type(s): plastics weight (kc		1.389				
P13.2*			kaging is free from PVC.	,			\boxtimes		
P13.3*	For pro consum	duct primary corrug	ated fiberboard packaging, specontent: %	cify the contained per	centage of minim	ium post-			
P13.4*		media for user and nic \bigotimes , Paper \bigotimes , C	product documentation (tick box): Dther						
P13.5	Úser an		tem if paper documentation used ation on paper media is chlorine-				\boxtimes		
	Elemen	chlorine-free tal chlorine-free sed chlorine-free							
P14		ary programs:							
P14.1	The pro	duct meets the requ	irements of the following voluntar	y program(s):					
	ENERGY STAR®Criteria version: 3.0Date:Product category: Colour printerEco-label: BAMCriteria version: RAL UZ 205Date:Product category: Colour printerEco-label:Criteria version:Date:Product category: Colour printerBate:Product category:Date:Product category:								
P15		nal information (Se			<u> </u>				
		•	·						

NOTE B10 A Guidance document on Chemical Emissions is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1